

1 TITLE

2

3 Machine, process and manufacture for synchronizing data across integrated  
4 applications

5

6 CLAIM OF PRIORITY/CROSS REFERENCE OF RELATED  
7 APPLICATION(S)

8

9 Not applicable

10

11 STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR  
12 DEVELOPMENT

13

14 Not applicable.

15

16 REFERENCE OF AN APPENDIX

17

18 Appendices A-B are contained herein. A portion of the disclosure of this patent  
19 document may contain material, which is subject to copyright/trademark  
20 protection. The copyright/trademark owner has no objection to the facsimile  
21 reproduction by anyone of the patent document or the patent disclosure, as it

1 appears in the Patent and Trademark Office patent file or records, but otherwise  
2 reserves all copyright/trademark rights whatsoever.

3

4

## 5 BACKGROUND

6

### 7 1. Field of the Invention

8

9 The present invention relates generally to data processing and more particularly,  
10 to a novel machine, process and manufacture for synchronizing data across a  
11 plurality of integrated applications.

12

### 13 2. Description of Related Art

14

15 Application integration is the process of bringing data or a function from one  
16 application program together with that of another application program.

17 Implementing application integration has previously been a tedious process  
18 involving long development and programming hours. However, the current trend  
19 is to use specialized integration products (prepackaged "middleware" solutions),  
20 such as message brokers and applications servers, to provide a common  
21 connecting point among disparate applications.

1

2 Several patents and publications disclose various application integration methods,  
3 portions of which are briefly summarized as follows:

4

5 U.S. Patent No. 6,236,994 entitled "Method and apparatus for the integration of  
6 information and knowledge," issued on May 22, 2001 to Swartz, et al., and  
7 discloses a method and apparatus for "integrating the operation of various  
8 independent software applications directed to the management of information  
9 within an enterprise. The system architecture is, however, an expandable  
10 architecture, with built-in knowledge integration features that facilitate the  
11 monitoring of information flow into, out of, and between the integrated  
12 information management applications so as to assimilate knowledge information  
13 and facilitate the control of such information. Also included are additional tools  
14 which, using the knowledge information enable the more efficient use of the  
15 knowledge within an enterprise, including the ability to develop a context for and  
16 visualization of such knowledge."

17

18 U.S. Patent No. 6,256,676 entitled, "Agent-adapter architecture for use in  
19 enterprise application integration systems," issued on July 3, 2001 to Taylor, et  
20 al., and discloses "an agent-adapter architecture used in systems and methods to  
21 integrate applications of the type normally deployed across a networked



1

2 Further objects of the present invention include, but are not limited to:

- 3 1) providing a link to a “vertical” integration mechanism to enable the  
4 horizontally integrated applications to integrate with other platform resources,  
5 such as mainframes and servers (Unix and NT), 2) streamlining workflows,  
6 3) eliminating redundant data, 4) move data among integrated applications with  
7 minimal effort, 5) linking data records and synchronizing linked data records  
8 across applications, 6) providing a migration path to a future state, and  
9 7) minimizing data required by applications.

10

11 Therefore in accordance with one aspect of the present invention, there is  
12 generally provided an apparatus, method and article of manufacture for  
13 integrating a plurality of heterogeneous applications using a common integration  
14 architecture wherein said apparatus, method and article of manufacture employs a  
15 Links Table for associating related data. Utilization of the Links Table enhances  
16 processing time over those techniques that search cumbersome data stores of  
17 integrated applications for relevant information during synchronization.

18

19 The above-mentioned aspect(s) and other aspects, objects, features and  
20 advantages of the present invention will become better understood with regard to  
21 the following description, appended claims, and accompanying drawings.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21

BRIEF DESCRIPTION OF THE DRAWING(S)

Referring briefly to the drawings, embodiments of the present invention will be described with reference to the accompanying drawings in which:

- FIG. 1 is a general representation of various components that comprise an integration architecture constructed in accordance with the teachings herein;
- FIG. 2 depicts an exemplary message structure in accordance with the teachings herein;
- FIG. 3 depicts an exemplary user interface in accordance with the teachings herein;
- FIG. 4 depicts an exemplary synchronization flow in accordance with the teachings herein;
- FIGS. 5-10 each depict a detail of the flow set forth in FIG. 4;

1 FIG. 11 depicts a Links Table in accordance with the teachings herein.

2

3 FIGS. 12-16 depict exemplary application flows in accordance with the teachings  
4 herein.

5

6 FIGS. 17-22 are representations of user interface screens depicting aspects of the  
7 present invention.

8

9

## 10 DETAILED DESCRIPTION

11

12 Referring more specifically to the drawings, for illustrative purposes the present  
13 invention is embodied in the system configuration, method of operation and  
14 product or computer-readable medium, such as floppy disks, conventional hard  
15 disks, CD-ROMS, Flash ROMS, nonvolatile ROM, RAM and any other  
16 equivalent computer memory device, generally shown in Figures 1 – 22. It will  
17 be appreciated that the system, method of operation and product may vary as to  
18 the details of its configuration and operation without departing from the basic  
19 concepts disclosed herein.

20

## 21 GLOSSARY

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21

In describing the present invention, the following terms are used herein.

“Data store” is a place where information is saved, preferably, in a persistent manner (e.g. on a hard drive). It may include relational databases, flat files, and proprietary storage formats.

“Horizontal integration” is integration across a single platform as opposed to integration between different platforms (e.g. client and server).

Integration software refers to the software/components used to synchronize information between applications.

“IOD” or “Integration on demand” is a user-driven approach to integration and not an automated replication model.

Vertical integration is integration between two or more platforms.

Working Client is that person whose information is designated as the current working set for any particular application and may not necessarily be a “client” of the enterprise as that term is used herein.

1

2

### 3 INTEGRATED ARCHITECTURE

4

5 To facilitate the integration and synchronization of required information, aspects  
6 and features of the present invention are embodied in a common integrated  
7 architecture. FIG 1, illustrates on example of such an integrated architecture 100  
8 constructed in accordance with the teachings presented herein. As shown, the  
9 integrated architecture comprises several interrelated components, namely an  
10 Integration Engine having an Integration Engine Service Adapter and an  
11 Integration Engine Data Store associated therewith (collectively enumerated as  
12 105), a plurality of Applications having associated Application Service Adapters  
13 and Application Data Stores (collectively enumerated as 110), Messages 115  
14 having a predefined syntax, and a Dashboard user interface 120, all arranged in a  
15 logical hub-and-spoke configuration.

16

17 Together the Integration Engine, its Service Adapter and Data Store, function as  
18 the “hub” of the architecture. Responsibilities of the integration engine include  
19 routing messages between service adapters based on type or content, transforming  
20 a message or message content based on the requirements of the integrated  
21 applications, and controlling the flow of information between service adapters.

1

2 The predefined Messages form the spokes. The content of every Message  
3 conforms to a standard syntax. All applications/resources produce and consume  
4 Messages that conform to a standard syntax, thus the present solution supports  
5 “plug-and-play” capabilities.

6

7 Finally, the Applications and the Application Service Adapters are the ends of the  
8 spokes. Depending on a particular task, Application Service Adapters can either  
9 serve as sources or as destinations and are responsible for accessing  
10 applications/resources to retrieve requested information and transforming this  
11 information into a common syntax and back again to its original format.

12

13 Attention now turns to details of the aforementioned components.

14

15

## 16 INTEGRATION ENGINE

17

18 The Integration Engine, its Service Adapter and Data Store are situated at center  
19 of the architecture. Together, these integration components implement intelligent  
20 messaging by triggering and executing integration flows to process events and  
21 rules that evaluate, modify, and route event data. Specific responsibilities include

1 setting application definitions for integrated applications, setting Dashboard's  
2 settings, and implementing updates and/or additions to the Links Table (see  
3 below).

4

5 The Integration Engine's Service Adapter can be called directly from the  
6 Dashboard or the integration flows.

7

8 The design specification for the Integration Engine Service Adapter is set forth as  
9 Appendix B.

10

11

## 12 APPLICATION SERVICE ADAPTERS

13

14 An adapter is an access point (logic) logic that provides access to the application  
15 in a structured manner. Thus, an adapter is an interface into the application that  
16 defines the requests the receiver will accept while hiding the underlying  
17 complexity of accomplishing the integration.

18

19 The Application Service Adapters herein are built to be plug and play with the  
20 system. That is to say, a new Application Service Adapter can be plugged in and

1 removed from the architecture without impacting the remaining Application  
2 Service Adapters.

3

4 Each application has its own data requirements. Typically, data requirements will  
5 not match from application to application. Therefore, it is the responsibility of the  
6 Application Service Adapter to understand and provide services to its underlying  
7 data store and further perform the necessary business logic to the data being  
8 passed to or retrieved from it.

9

10 While all Application Service Adapters speak in a standard syntax, nonetheless  
11 should an application require another standard, it can easily be supported by the  
12 transformation capabilities of the Integration Engine. To that end, the Integration  
13 Engine communicates with the Application Service Adapters via predefined  
14 Messages (see below).

15

16 The design specification for an Application Service Adapter is set forth as  
17 Appendix C.

## 1   MESSAGES

2

3   The predefined Messages recognized by the present invention form the spokes in  
4   the integrated architecture. In FIG 3, for visual simplicity, the spokes also include  
5   the technology transport of the messages. The content of every Message conforms  
6   to a standard syntax. Specifically, the structure of the Messages created and  
7   processed in the present invention may be logically divided into three main  
8   sections, a Message Root section 202, a Message Envelope section 204 and a  
9   Message Body section 206. The Message Envelope section is further divided into  
10   a Source section 208 and a Destination section 210. The Message Body section  
11   is further divided a Parameters section 212 and a Payload section 214. The  
12   Payload section is still further divided into a Status section 216, a Links section  
13   218, and a Pay Load Item section 220. Each of the foregoing sections and  
14   subsections will now be further explained below.

15

### 16   1. Message Root

17

18   The Message Root section contains header information about a given message.

19   The Message Root comprises an IONS identifier (IONSID) field and a message

1 request type (RequestType) field. A description of each of the foregoing fields  
2 follow.

3

4	<u>Property</u>	<u>Description</u>
5	IONSID	A unique identifier for a user, e.g., the
6		user's Windows® operating system login
7		id.
8		
9	RequestType	The name/type of the request message, e.g.,
10		GetPerson_RQ message or SyncPerson_RQ
11		message. See Appendix A for additional message
12		types.

13

## 14 2. Message Envelope

15

16 The Message Envelope section comprises a Source section and a Destination  
17 section containing routing information, which lets the Integration Engine know  
18 which Service Adapter(s) to send the message to. In cases where source

1 information is not needed, the initiator of the message need not supply source  
2 information.

3

4 Note: in order to maintain the principle that a user should have exactly the same  
5 rights to the information in an application data store that they have when using the  
6 application itself, we must maintain information about users.

7

#### 8 A. Source

9

10 The Source section consists of several fields having information pertaining to the  
11 Service Adapter of the Source Application. The relevant fields are described  
12 below.

13

14 <u>Property</u>	<u>Description</u>
15	
16 DataSourceDescription	A description of the data source, usually the
17	ODBC DSN or a File Name.
18	
19 Name	The name of the Service Adapter.

20

1	UserID	An application user
2		identifier. Note: This is not the IONSID
3		mentioned above.
4		
5	Password	An application user password associated
6		with the UserID. The password is used to
7		validate an applications settings when a user
8		customizes the Dashboard. There is no
9		requirement to store the password.

11 B. Destination

12

13 The Destination section consists of several fields having information pertaining to

14 the Service Adapter of the Destination Application. The relevant fields are

15 similar to that of the Source section and are described below.

17	<u>Property</u>	<u>Description</u>
18		
19	DataSourceDescription	A description of the data source,
20		usually the ODBC DSN or a File Name.

21



1 A. Parameters

2

3 The Parameters section contains the parameters that a message requires. In cases  
4 where a message does not utilize a parameter this section will be blank. The  
5 Parameters section comprises two fields, which are described below.

6

7	<u>Property</u>	<u>Description</u>
8	Name	The name of the parameter
9	Value	The value of the parameter.

10

11 B. Payload

12

13 The Payload section contains the results of the message request. The Payload  
14 section divides into three sub-sections, namely a Status section, a Links section  
15 and a Payload Items section. The foregoing sub-sections are described below.

16

17 i. Status

18

19 The Status section contains information related to the completion of the message.  
20 If the message is successful, it will contain a status code and description  
21 indicating success. It is also here that you will find information about any errors

1 that were encountered during the messages execution. There can be many  
2 occurrences of this section. The Status section comprises several fields, each of  
3 which are described below.

4

5 Property                      Description

6

7 StatusCode                      The status code of the error.

8

9 Description                      A description of the error.

10

11 OriginatedFrom                      The name of the dynamic link library (DLL) that the error  
12 occurred in.

13

14 ModuleName                      The name of the module that the error occurred in.

15

16 MethodName                      The name of the method where the error occurred.

17

18

19 ii. Links

20

1 The Links section is utilized during synchronization. Among other information,  
2 the Links section contains a record of a Service Adapter's actions, that is whether  
3 an "Add" or "Update" was done. In addition, it contains certain information a  
4 Service Adapter needs during processing, for example, the unique identifiers  
5 assigned to the Source and Destination Applications. The Links section  
6 comprises several fields, each of which are described below.

7

8 <u>Property</u>	<u>Description</u>
9	
10 DataSourceDescription	A description of a data source, usually the
11	ODBC DSN or a File Name
12	
13 Name	The Service Adapter's name
14	
15 *SourceID	A unique identifier for the object, e.g. a
16	person or an organization, in the
17	Source Application
18	
19 *DestinationID	A unique identifier for the object in the
20	Destination Application.

21

1	*PartyID	A unique identifier for the object within
2		the system.
3		
4	*ObjectType	Identifies the object as a person or an
5		organization.
6		
7	*ActionPerformed	The action that the Service Adapter
8		performed on the object, e.g., “Add” or
9		“Update”

11 \* These properties can occur multiple times.

### 13 iii. Payload Item

15 The Payload Item section contains the results of a request. For example, a  
 16 receiver of a Search\_RQ request message would place the search results in the  
 17 Payload Item section of a response message. There can be one or more instances  
 18 of a payload item. Since a request can be sent to multiple destinations, to track  
 19 what part, or “item”, in the payload came from a particular Service Adapter the  
 20 following properties/fields are included at the beginning of each Payload Item  
 21 section.

1

2     Property                      Description

3

4     DataSourceDescription        The description of a data source. Usually the  
5                                      ODBC DSN or a File Name.

6

7     Name                          The Name of the Service Adapter

8

9     The rest of Payload Item section varies based on the request. Specific message  
10    types used herein are set forth in the Appendices.

11

12

13    USER INTERFACE

14

15    The present system includes a graphical user interface that enables a user to work  
16    with the aforementioned integration flows.

17

18    Accordingly, FIG. 3 depicts an exemplary embodiment of an “Integrated Client  
19    Dashboard” graphical user interface (“Dashboard”) utilized in the present  
20    invention. The Dashboard is designed to facilitate user-driven data integration  
21    across integration Applications via a flexible application workflow model.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21

For example and referring to the insurance industry, a user who starts the sales process by entering information in a prospecting application (CDS) and then moves on to discovery and analysis using a discovery application (DIS) and an analysis application (PAS) can use the Dashboard to move client information from the CDS to DIS/PAS applications by activating the buttons on the Dashboard. Similarly, an alternative workflow is also supported wherein a user begins prospecting by enter information into illustrations application (ISP) and then moves to the discovery application.

As shown, the look and feel of the illustrated embodiment of the Dashboard is based on the look and feel of the popular Shortcut Bar used in Microsoft® Office suite. The Dashboard spans the length of the display device and is initially situated at the bottom of the display medium, such as a window object or computer screen. However, as is conventional, the Dashboard may be resized and also positioned elsewhere on the display device as preferences dictates.

The Dashboard includes several areas, namely a Menu Access area 302, an Integration area 304, a Non-Integrated area 306, and a Status area 308, which together invoke aspects and features of the present invention. The details of each of these areas will now be discussed.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21

Menu access area

The Menu access area comprises a Menu Access button. Upon selection of the Menu access button a menu bar appears like that shown in FIG. 22. As indicated, the menu bar provides access to certain commands/functions, for example, Auto Hide, Customize, Help and Exit, that control certain aspects of the instant invention. The Auto Hide command enables the Dashboard to reside behind other applications displayed on the display device. The Customize command allows the user to alter settings for the Dashboard, for example, adding/removing application files to/from the Dashboard, modifying information about a particular application, and modifying other attributes of the Dashboard, including color and size.

Selecting the Help command launches the Help facility and selecting the Exit command exits the Dashboard. Other commands/function may also be displayed.

Integration area

The Integration area is a collection of buttons that serve as shortcuts for executing and controlling the synchronization process describe herein.

1

2 For example, the embodiment shown in FIG. 3 depicts, a Help button (A), a  
3 Search button (B), a MultiSync button (C) and several buttons representing  
4 applications integrated with the present system (D-H).

5

6 Selecting the Search button launches a search applet for searching integrated  
7 applications. The search applet returns and displays results based on the search  
8 criteria entered. Using the returned results a user may take the following actions:  
9 1) select a Working Client causing information about the Working Client to  
10 appear in Status area of the Dashboard); 2) select the Working Client and view all  
11 data relating to the Working Client, and 3) select a Working Client and launch  
12 directly to the application where the client resides.

13

14 Selecting the MultiSync button synchronizes data from Source to Destination  
15 Applications.

16

17 Selecting any one of the integrated application buttons will process the Working  
18 Client's information in accordance with the teachings expressed herein, for  
19 example, push data from a source to the selected integrated application.

20

21 Non-Integrated area

1

2 The non-integrated area includes a non-integrated application button and one or  
 3 more specific application/website buttons. Upon selection of the non-integrated  
 4 application button, a drop down list appears. The drop down list sets forth at least  
 5 all external, non-integrated applications/web sites having buttons appearing on the  
 6 Dashboard. Selecting any one of the application/website buttons will launch the  
 7 particular application/website.

8

9 Status area

10

11 The Status area displays information that is relevant to the current Working  
 12 Client, for example, the name of and the Working Application containing the  
 13 Working Client.

14

15 When the Dashboard restarts, it will retain all prior settings at shut down  
 16 including the Working Client and Working Application information and the  
 17 Dashboard's last position on the display device

18

19 Other features/embodiments of the Dashboard

20

1 The Dashboard, in its most basic embodiment, may be customized to only consist  
2 of a Menu Access area, an Integration area and a Status Area and yet still retain  
3 the desired functionality.

4

5 In alternative embodiments of the Dashboard, certain areas of the Dashboard will  
6 display hover text indicating the function of the area. For example, to display the  
7 function of the Multi Sync button, a user positions the mouse over the button for a  
8 few moments to generate a hover text stating "Send Working Client to Multiple  
9 Applications."

10

11 Further, when a user right-mouse-button clicks anywhere on the Dashboard, the  
12 system displays a shorter, modified menu bar. This menu has three of the same  
13 functions as the regular menu – Auto Hide, Customize, and Exit. These behave  
14 exactly the same as on the regular menu.

15

16

## 17 DATA SYNCHRONIZATION

18

19 An application of the present solution will now be described with reference to  
20 FIGS. 4-11. The sections that follow demonstrate how customer demographic  
21 information is modified across several integrated heterogeneous applications.

1

2 FIG. 4 depicts a high level view of an exemplary data synchronization flow in  
3 accordance with the principles expressed herein comprising several interrelated  
4 software modules, namely, a Set Working Client & Application module 400, a  
5 Verify Links module 402, a Find Matches module 404, a Verify Destination  
6 Application Availability module 406 and a Synchronization module 408.

7

8 When a user clicks on an application icon on the Dashboard signaling data  
9 synchronization, an integration request message is generated by the dashboard  
10 and sent to the Integration Engine where certain pre-processing steps are first  
11 performed before the integration request message is handled. An integration  
12 request message is a template by which all the messages described herein are  
13 derived from. The messages have a certain attributes that are the same regardless  
14 of what type of request is being made (for example, whether the request is a  
15 Search, Sync, etc.). Specifically, all messages have the following properties,  
16 IONSID, REQUEST\_TYPE, SOURCE, DESTINATION, PARAMETERS.

17

18 As shown in FIG. 4, to begin synchronization, the Set Working Client &  
19 Application module executes. This module performs the pre-processing steps of  
20 verifying whether a desired Working Client has been properly selected and  
21 whether a desired Working Application (Source Application) is available for

1   synchronization. If true, the Verify Links module 4 is dynamically created (see  
2   below) and utilized as a basis for the synchronization flow.

3  
4   If the Working Client is properly set and the Source Application is available for  
5   synchronization, the Verify Links module 402 executes. This module is  
6   dynamically created and utilized as a basis for the synchronization flow.

7   Specifically, this module first verifies that signatures exist in the Destination  
8   Application data store. For example, when a signature check is performed, a  
9   getSignature message is constructed and sent to a Destination Application's  
10   Service Adapter. Next, an attempt to retrieve the links for the Working Client in  
11   both the Source and Destination Applications is performed against the Integration  
12   Engine's database.

13  
14   Attention will now turn to the Links Table as that data structure is used herein. A  
15   dynamic Link Table like that shown in FIG. 11 is populated whenever a user  
16   establishes links among integrated applications for a particular  
17   customer/person/client. As shown, the Link Table has five columns entitled, Link  
18   Key, User Application Id, Party Id, Client Id and Last Sync Date.

19

1 The Link Key column contains unique identifiers associated with each row in the  
2 Link Table. In the present example, each row is number sequentially. Thus, row  
3 one has a link key of 1, row 2 has a link key of 2 and so on.

4  
5 The User Application Id column contains unique identifiers associated with the  
6 integrated applications. Thus, in the example illustrated in FIG 11, the CDS  
7 application is assigned a user application id of 5, the ISP application is assigned a  
8 user application id of 6 and the PAS application is assigned a user application id  
9 of 7.

10  
11 The Party Id column contains global identifiers associated with each  
12 customer/person/client in the Integration Engine data store. Thus, in the example  
13 illustrated in FIG. 11, customer/client/person William Brown is assigned a party  
14 id of 2 and customer/client/person J. Doe is assigned a party id of 2. Notably, a  
15 glance down the Party Id column immediately tells a reviewer that only two  
16 people are currently linked in the Integration Engine data store.

17  
18 The Client Id column contains unique identifiers associated with  
19 customers/clients/persons in their respective native applications. Thus, in the  
20 example illustrated in FIG. 11, the CDS application assigns  
21 customer/client/person W. Brown a client id of 20 and assigns

1 customer/client/person J. Doe a client id of 200. The PAS application assigns a  
2 client id of 20 to customer/client/person W. Brown and assigns  
3 customer/client/person J. Doe a client id of 200.  
4

5 The Last Sync Date column sets forth the most recent date synchronization was  
6 done for a particular customer/clients/person. Thus, in the example illustrated in  
7 FIG. 11, data was last synchronized in the CDS application for  
8 customer/client/person W. Brown on 1/18/01 and in the ISP and PAS applications  
9 on 5/22/01. For customer/client/person J. Doe, data was last synchronized in the  
10 CDS and PAS applications on 2/4/01.  
11

12 Due to the inherent nature of technology, unforeseen glitches may occur and as a  
13 result cause an application's data to become corrupted. However, once an  
14 application's data is restored, all of the unique identifiers in the application's data  
15 store will change where the identifier is a sequentially generated one.

16 Consequently, the identifiers will no longer match what is stored in the Link table  
17 for that application data store.  
18

19 Without correction, a synchronize action will associate and overlay information  
20 with the wrong individual/object/item in the application's data store.  
21

1 Because of the necessity to provide correct and consistent information, the present  
 2 invention provides for the Links Table to be updated whenever a particular  
 3 application's data store has been corrupted, reloaded or refreshed.

4  
 5 The first time an application's data store is used, a signature record should be  
 6 written into the data store where the data store uses a unique identifier for an  
 7 individual/item/object that will change upon a data reload (e.g. have a  
 8 sequentially generated unique identifier).

9  
 10 The unique identifier for the signature record is recorded in the link table.

11 On start up, a check of all signature records will be performed. If a signature  
 12 record does not exist in one or more application data stores, an error message is  
 13 generated display an information and warning message for each application such  
 14 as "XYZ data appears to have been refreshed. Links are no longer valid. Do you  
 15 want to clear all links for this application?" If a user selects "Yes", the link table  
 16 entries for that application are reset and a new signature record is written to the  
 17 application data store. If "No" is instead selected, all add and update actions for  
 18 that application is disabled. For example and referring to FIG 11, if the CDS  
 19 application's data store was corrupted and subsequently refreshed and a user  
 20 selects Yes, all links for CDS in the Links Table, that is Rows 1 and 4, would be

1 removed and replaced with updated information. If a user selects No the user will  
2 unable to use the CDS application button on the Dashboard for synchronization.

3

4

5 Referring back to FIG. 4, if no links for the Working Client in the Source and  
6 Destination Applications were found in the Verify Links module 402, the Find

7 Matches module 404 executes. Otherwise, the Find a Match module 404 is

8 bypassed and control passes to the Verify Destination Application Availability

9 module 406. The Find Matches module 404 searches within data stores

10 associated with selected Destination Applications to locate information matching

11 that of the Working Client.

12

13 Next, the Verify Destination Application Availability module 406 executes. This

14 module determines whether the desired Destination Application(s) is/are currently

15 available for synchronization. If true, a SyncPerson\_RQ message will be created

16 (see below) and utilized in the Synchronization module described below.

17

18 Finally, the Synchronization module 408 executes. This module, among other

19 things, performs the desired task of synchronizing data from the Source

20 Application to the desired Destination Application(s).

21

1 For a better understanding of the present solution, the above modules will now be  
2 further described in the sections that follow.

3

4

5 Set Working Client and Application

6

7 Referring to FIG 5, there is shown an exemplary block diagram detailing an  
8 exemplary process flow of the Verification module in accordance with the  
9 principles expressed herein.

10

11 In response to an integration request message, a determination is first made as to  
12 whether the desired Working Client is set. If the Working Client is not set,  
13 execution terminates and in one embodiment of the present solution, an error  
14 message is generated indicating that the Working Client is not set. If, on the other  
15 hand, the Working Client is set then a determination is made as to whether a  
16 selected Working Application is available for data synchronization. During the  
17 synchronization process, the Working Application will serve as the Source  
18 Application. If the Source Application is not available for data synchronization,  
19 execution terminates and in one embodiment of the present solution, an error  
20 message is generated indicating that the Working Application is not available for  
21 synchronization. However, if the Working Application is available for

1   synchronization, the Verify Links module will be dynamically constructed based  
2   upon the original integration request message.

3

4   That is to say, in preparing the Verify Links module, certain information is  
5   extracted from the original integration request message and included in the Verify  
6   Links module, but not limited to, the Working/Source Application, the Working  
7   Client, and all Destination Applications.

8

9   Finally, after the Working and Client applications have been properly verified and  
10   the Verify Links module constructed, control passes to the next module in  
11   sequence.

12

13   Verify Links

14

15   Upon completion of the Verification module, the Verify Links module executes in  
16   accordance with the following exemplary process flow.

17

18   In one embodiment of the present invention, the Verify Links module logically  
19   divides into two sub-processes. First, signatures are checked and second, links  
20   between the Working Client and Destination Applications(s) are checked in  
21   accordance with the following exemplary process flow.

1

2 A. Check Signatures in Destination Application's Data Store

3

4 Referring to FIG. 6, first, the Integration Engine's Service Adapter constructs a

5 GetSignature\_RQ message based upon the contents of the VerifyLinks message.

6 Specifically, the Integration Engine's Service Adapter constructs a

7 GetSignature\_RQ message for each application contained in the Source and

8 Destination sections of the VerifyLinks message envelope and transmits the same

9 to the Service Adapters of the Destination Application(s).

10

11 Next, in response to the GetSignature\_RQ message, each Destination

12 Application's Service Adapter determines whether a signature already exists in

13 the Destination Application's data store and whether the Destination

14 Application's Service Adapter supports the integration request message. In

15 determining whether a signature exists, the Service Adapter checks the value in

16 the Status Code section of the GetSignature\_RQ message. If a signature does not

17 exist, then the Destination Application's Service Adapter constructs a

18 ClearLinks\_RQ message for the Destination Application and execution control

19 returns to process the next Destination Application contained in the

20 GetSignature\_RQ message. If the Service Adapter supports the integration request

21 message, the Destination Application's Service Adapter constructs a

1 ClearLinksByDate\_RQ message for the Destination Application and execution  
 2 control returns to process the next Destination Application contained in the  
 3 GetSignature\_RQ message.

4

5 If the Destination Application's Service Adapter supports the integration request  
 6 message but the relevant signature does not exist in the Destination Application's  
 7 data store, both the ClearLinks\_RQ and the ClearLinksByDate\_RQ messages are  
 8 transmitted to the Integration Engine's Service Adapter. In response to the two  
 9 messages, the Integration Engine's Service Adapter constructs an

10 AddSignature\_RQ message and transmits the message to the Destination

11 Application contained in the ClearLinks\_RQ message. In response to the

12 AddSignature\_RQ message, the Destination Application's Service Adapter will

13 add the signature to the Destination Application's data store. The foregoing

14 process is done for all Destination Applications wherein the Destination

15 Application's Service Adapter supports the integration request message but the

16 relevant signature does not exist in the Destination Application's data store.

17

18 B. Check Links using Links Table

19

20 Referring to FIG. 7, after signatures have been checked, links between the

21 Working Client and Destination Applications(s) are also checked.

1

2 First, the Integration Engine's Service Adapter constructs a CheckLinks\_RQ  
3 message based upon information derived from the original integration request  
4 message and transmits the same to the Destination Applications. The  
5 CheckLinks\_RQ message will check to see if a link or links for the Working  
6 Client/Person exist between the Source Application and the Destination  
7 Application.

8

9 In response to the CheckLinks\_RQ message and for each Destination Application  
10 contained in the message envelope of the CheckLinks\_RQ message, the  
11 Integration Engine's Service Adapter will check the Links Table to determine  
12 whether a link for the Working Client/Person exists between the Source  
13 Application and the Destination Application. A CheckLinksResponse message is  
14 then constructed and transmitted indicating the results of the query.

15

16

17 Find Matches

18

19 Referring to FIG. 8, the Find Matches module executes, if required, in accordance  
20 with the following exemplary process flow. Note the Find Matches module  
21 executes only if no link was found in the previous module.

1

2 For each Destination Application contained in the message envelope of the  
3 original integration message, the following steps occur:

4

5 First, the Integration Engine Service Adapter constructs and transmits a  
6 ServiceAvailable\_RQ message to the Destination Application's Service Adapter  
7 to determine whether the Destination Application is available for synchronization  
8 and more particularly, whether the Destination Application's Services are  
9 available.

10

11 If the response to the ServiceAvailable\_RQ message is positive (that is the  
12 Destination Application has synchronization capability), The Integration Engine  
13 Service Adapter issues a GetPersonDetails\_RQ message to the Source  
14 Application's Service Adapter. In response to GetPersonDetails\_RQ message,  
15 the the Source Application's Service Adapter retrieves and transmits the desired  
16 customer demographic information. If, however, the Destination Application's  
17 Services are not available, execution terminates and, in one embodiment of the  
18 present solution, an error message is generated indicating that the Destination  
19 Application is not configured for synchronization.

20

1 Next, a determination is made as to whether a link exists for the Working Client  
2 between the Source Application and the Destination Application.

3  
4 If a link exists for the Working Client between the Source Application and the  
5 Destination Application, then execution control passes to the next module in  
6 sequence, namely the Determine Destination Application Availability module.

7  
8 If, on the other hand, there is no link for the Working Client between the Source  
9 Application and the Destination Application, the Destination Application's  
10 Service Adapter searches the Destination Application's data store to find a  
11 potential Matching Client for the Working Client using the following exemplary  
12 search criteria: Social Security Number, Date of Birth, Last Name, and First  
13 Name. This process is done to avoid duplicate entries of the Working Client in  
14 the Destination Application's data store. Note: the Working Client may in fact  
15 exist in the Destination Application's data store but a link may not exist for the  
16 Working Client between the Source Application and the Destination Application.  
17 If there are no potential Matching Clients, execution control passes to the next  
18 module in sequence, namely the Determine Destination Application Availability  
19 module.

20

1 If one or more potential Matching Clients are found, they are displayed to the  
2 user. The user is then provided with three options.

3  
4 Option 1: The user wishes to add the Person because none of the potential  
5 Matching Clients actually matches the Working Client;

6  
7 Option 2: The user desires to update and link the Person because at least one of  
8 the potential Matching Clients actually matches the Working Client; or

9  
10 Option 3: The user cancels and control is returned to the Dashboard.

11  
12 Referring to options 1 and 2, if the user selects option 1, execution control passes  
13 to the next module in sequence. If the user selects option 2, a determination is  
14 made as to whether a link for the Working Client between the Source Application  
15 and the Destination Application exists in the Integration Engine's Database.

16  
17 Outcome 1 – No link For Working Client Exists in the Integration Engine's  
18 Database

19  
20 If there are no links for the Working Client in the Integration Engines database, a  
21 determination is then made as to whether a link for the selected Matching Client

1 between the Source Application and the Destination Application exists in the  
2 Integration Engine data store via the Verify Links module.  
3  
4 In response to the CheckLinks\_RQ message, the Integration Engine's Service  
5 Adapter will check the Links Table to determine whether a link for the Matching  
6 Client exists between the Source Application and the Destination Application. A  
7 CheckLinksResponse message is then constructed and transmitted indicating the  
8 results of the query.  
9  
10 If a link for the selected Matching Client exists, an UpdateLinks message is  
11 constructed and executed resulting in a link being created between the Working  
12 Client in the source application and the selected Matching Client in the  
13 Destination Application. Note: Since a link already exists, the PartyID of the link  
14 for the person selected will be used when creating link. Thereafter, execution  
15 control returns to the beginning of the iterative loop to process the next  
16 Destination Application contained in the message envelope of the original  
17 integration request message.  
18  
19 If, on the other hand a link for the selected Matching Client does not exist in the  
20 Integration Engine data store, an UpdateLinks message is constructed and  
21 executed, resulting in a link being created between the Working Client in the

1 Source application and the selected Matching Client in the Destination  
2 Application. Note: Since no link existed for the Working Client or selected  
3 Matching Client, a new PartyID will be created upon completion. Thereafter,  
4 control returns to the beginning of the iterative loop to process the next  
5 Destination Application contained in the message envelope of the original  
6 integration request message.

#### 7 8 Outcome 2 – Link for the Working Client Exists

9  
10 If a link for the Working Client exists in the Integration Engine data store, an  
11 UpdateLinks message is created and executed resulting in a link being created  
12 between the Working Client in the Source Application and the selected Matching  
13 Client in the Destination Application. Note: Since a link already exists, the  
14 PartyID of the link for the working client will be used when creating link.  
15 Thereafter, execution control returns to the beginning of the iterative loop to  
16 process the next Destination Application contained in the message envelope of the  
17 original integration request message.

18  
19 After all Destination Applications contained in the message envelope of the  
20 original integration request message having been processed, execution control  
21 passes to the next module in sequence.

1

2

3 Determine Destination Application Availability

4

5 Referring to 9, upon completion of the preceding modules, the Verify Destination

6 Application Availability module executes in accordance with the following

7 exemplary process flow.

8

9 First, a SyncPerson\_RQ message is prepared based on the original integration

10 request message as follows: the Source Application of the SyncPerson\_RQ

11 message is set to the Source Application of the original integration request

12 message and the Working ClientID of the original integration request message is

13 used as a parameter of the SyncPerson\_RQ message.

14

15 For each Destination in the Destinations Section of the

16 SyncPerson\_RQ message the following steps occur:

17

18 First, a determination is made as to whether the Destination Application's

19 Services are available by issuing a ServiceAvailable\_RQ Message to the

20 Destination Application Service Adapter.

21

1 If the Destination Application's Services are available, the Destination  
 2 Application is added to the message envelope (that is, the Destinations section) of  
 3 the SyncPerson\_RQ message. Thereafter, execution control returns to the  
 4 beginning of the loop to process the next Application requiring synchronization.

5

6 If the Destination Application's Services are not available, execution terminates  
 7 and, in one embodiment of the present solution, an error message is generated  
 8 indicating the same.

9

10 Finally, after all Destination Applications have been added to the message  
 11 envelope of the SyncPerson\_RQ message, control passes to the next module in  
 12 sequence.

13

## 14 5. Synchronization

15

16 Referring to FIG. 10, after the Verify Destination Application Availability module  
 17 has executed, control passes to the Synchronization module, which executes in  
 18 accordance with the following exemplary process flow.

19

20 First, signatures are checked via the Verify Links module (see above).

21

1 Next, a GetPerson\_RQ message is constructed based upon information derived  
2 from the SyncPerson\_RQ message as follows: the Destination Application of the  
3 GetPerson\_RQ message is set to the Source Application of the SyncPerson\_RQ  
4 message and the PersonID parameter of the SyncPerson\_RQ message is passed as  
5 a parameter of the GetPerson\_RQ message.

6

7 Next, the GetPerson\_RQ message is sent to the Service Adapter of the  
8 Destination Application. The Destination Application's Service Adapter retrieves  
9 the appropriate customer demographic data, constructs and transmits a reply  
10 message (GetClientResponse message ) having the requested demographic data.

11

12 Next, a GetLinks\_RQ message is constructed based upon information derived  
13 from the GetClientResponse message. The GetLinks\_RQ message retrieves other  
14 relationships linked to the desired person, such as mother, father, son, etc.

15

16 Next, the GetLinks\_RQ message is sent to the Integration Engine's Service  
17 Adapter. The Integration Engine's Service Adapter retrieves any existing linked  
18 relationships, constructs and transmits a GetLinksResponse reply message having  
19 the linked relationships

20

1 Next, an UpdateLinksRequest request message is constructed using information  
 2 derived from the original integration request message. (Note: at this stage in the  
 3 process, the SyncPerson\_RQ message is still being prepared for execution.)

4  
 5 Next, for each Destination Application in the Destinations section of the  
 6 SyncPerson\_RQ message, the following steps occur:

7  
 8 Next, the SyncPerson\_RQ message is further populated with the following  
 9 information: the Destination Application is loaded in the Destination section of  
 10 the SyncPerson\_RQ message, the payload of the GetClientResponse message  
 11 (having demographic information) is loaded in the Payload section of the  
 12 SyncPerson\_RQ message and the Links section of the GetLinksResponse  
 13 message is loaded in the Links section of the SyncPerson\_RQ message

14  
 15 Next, the SyncPerson\_RQ message is sent to the Destination Application's Service  
 16 Adapters. In response to the SyncPerson\_RQ request, the Destination  
 17 Application's Service Adapter retrieves the desired data from the data store of the  
 18 Destination Application (sync data from the Source Application's data store to the  
 19 Destination Application's data store), constructs and sends a  
 20 GetSyncPersonResponse reply message indicating if the synchronization was  
 21 successful or not. If an error was encountered during the processing, this error

1 will be included in the message along with information about the error itself, such  
2 as, number description, etc.

3

4 Next, the Link section of the UpdateLinks\_RQ message is updated to include the  
5 link information of the Links section of the GetSyncPersonResponse reply  
6 message.

7

8 Control returns to the beginning of the loop to process the next Destination  
9 Application in the Destinations section of the SyncPerson\_RQ request message.

10

11 After all Destination Applications have been processed (synched), the  
12 UpdateLinksRequest message is sent to the Service Adapter of the Integration  
13 Engine. In response to the UpdateLinks\_RQ request, the Integration Engine's  
14 Service Adapter uses the information stored in the Links section of the  
15 UpdateLinks\_RQ to update the Links Table. More particularly, once  
16 synchronization is complete, the SyncPerson\_RQ message will add or update the  
17 links for the Source and Destination(s) if necessary.

18

1    Thereafter, the Integration Engine's Service Adapter constructs and dispatches an  
2    UpdateLinksResponse reply message indicating whether the process was  
3    successful or not. If not, an appropriate error message will be returned.

4

5    Next, an UpdateSignature message is constructed for all applications in the Source  
6    and Destination sections of the SyncPerson\_RQ message, and dispatched to the  
7    Integration Engine's Service Adapter. The Service Adapter then adds the date of  
8    the synchronization to the Links Table.

9

10   Finally, in response to the UpdateSignature message, the Integration Engine's  
11   Service Adapter constructs and dispatches an Output message based on  
12   information derived from the SyncPerson\_RQ and UpdateLinks\_RQ messages.

13

14

## 15    ALTERNATIVE APPLICATION INTEGRATION FLOWS

16

17   FIGS. 12-16 depict alternative integration flows associated with certain aspects of  
18   the present invention.

19

1 In each figure, the integrated software architecture is divided into levels, namely  
2 several Application levels, a User Interface/Dashboard level, an Integration  
3 Services Level and a Data Source Level.

4  
5 As shown, the Application level contain standard native applications, namely,  
6 Application A, Application B as well as Other Applications. The User  
7 Interface/Dashboard Level contain the user interface. The Integration Services  
8 level contain the requisite integration components, such as the integration engine  
9 and service adapters. Finally, the Data Source Level contains the various data  
10 stores that are created, managed and stored for the purposes of synchronizing data  
11 across applications.

12  
13 Referring back to the figures, FIG. 12 depicts how a user, using a standard  
14 application (in this case, Application A), creates a client record for a new  
15 person/client/customer/prospect in accordance with the present invention. As  
16 evidenced by the illustrated flow, there is no interaction with any of the  
17 integration components of the system, that is the Dashboard or the Integration  
18 Services, during this process. Because of this, the integration components are  
19 unaware of the new client record. This situation would be accounted for in future  
20 work-flows by either the user or by the integration software.

21

1 Alternatively, FIG. 13 depicts how a user, using the Dashboard, creates a client  
 2 record for a new person/client/customer/prospect in accordance with the present  
 3 invention.

4  
 5 FIG. 14 depicts how a user, selects a Working Client using the Dashboard, in  
 6 accordance with the present invention. This integration flow assumes that the  
 7 selected Working Client already exists in the Link Table.

8  
 9 The flow of FIG. 15 depicts synchronization of a linked client and FIG. 16 depicts  
 10 how links between applications are established.

## 11 PRACTICAL APPLICATIONS

12  
 13  
 14  
 15 The following sections provide practical applications of the present solution in  
 16 order to fully appreciate features of the present solution.

17  
 18 In the use cases that follow, Agent Ms. Angie Baker will begin her workflow by  
 19 prospecting for a potential customer, a Mr. William R. Brown. Among the  
 20 various integrated applications on Ms. Baker's Dashboard include: a prospecting,  
 21 a discovery, an analysis application, an asset allocation application, a product

1 illustrations application and an electronic assistant application. For simplicity, the  
 2 foregoing applications shall hereinafter be referred to as a CDS application, a DIS  
 3 application, a PAS application, a PLAM application, an ISP application and EA  
 4 application, respectively. Ms. Baker's Dashboard also includes one or two  
 5 external, non-integrated applications, for example, a web browser application  
 6 such as Microsoft® Internet Explorer®.

7  
 8

9 Use Case 1: Creating a New Person and Pushing Information Into a Second  
 10 Application

11

12 This use case can take place over a period of several days or weeks. After  
 13 prospecting with the CDS application, Ms. Baker meets with a potential customer  
 14 or prospect, a Mr. William R. Brown, and gathers information about Mr. Brown  
 15 using the Discovery application. Ms. Baker further analyzes the prospects  
 16 information using the PAS application.

17

18 To propose insurance policies to the prospect, Ms. Baker moves on to ISP to  
 19 create illustrations of the products for the prospect. When the prospect chooses an  
 20 insurance policy and chooses to open an investment account, Ms. Baker uses the

1 PLAM application to capture required investor information. Finally, Ms. Baker  
2 uses the EA application to submit the new business information.

3  
4 After many days of calling Mr. Brown for a follow-up meeting, Ms. Baker finally  
5 sets up an appointment with Mr. Brown. Ms. Baker meets with Mr. Brown and  
6 gathers information about Mr. Brown and completes a paper-based Fact Finder on  
7 Mr. Brown during the meeting. Ms. Baker returns to her office to enter the Fact  
8 Finder data into the Discovery application.

9  
10 To begin entering the Fact Finder data into the Discover application, Ms. Baker  
11 clicks on the "Search" button of the Dashboard.

12  
13 The search dialog appears and Ms. Baker enters the name search criteria, such as  
14 "Brown" in the last name field and "William" in the first name field, selects the  
15 Source applications she wants to search (e.g. CDS, ISP), and clicks on the  
16 "Search" button. After Ms. Baker submits the search request, the results appear as  
17 a list of William Brown's found in the selected applications.

18  
19 Ms. Baker highlights the William Brown she wants to work with (from the CDS  
20 application database in this case since she first entered Mr. Brown's information  
21 in the CDS application) based on the information displayed (such as address and

1 Tax ID) and clicks on the "Working Client" button, thereby setting William R.  
 2 Brown as the current client. The "Working Client: William R. Brown (CDS:)" is  
 3 then set and indicated in the Status area of the Dashboard. Note: the term  
 4 "Working Client" refers to both customers and prospects.  
 5  
 6 Ms. Baker then clicks on "PAS/Discovery" button. A dialog box opens asking  
 7 "This action will create information about the Working Client in PAS/Discovery.  
 8 Do you want to continue?" Ms. Baker sees a "Yes" button, a "No" button, and a  
 9 check box titled "Don't ask anymore. Just do it." Ms. Baker has become familiar  
 10 with the Dashboard interface and checks the "Don't ask" check box. If William R.  
 11 Brown records were already in the PAS/Discovery applications, the dialog box  
 12 would have said "This action will update existing information about the working  
 13 client in PAS/Discovery. Do you want to continue?" The existence of William R.  
 14 Brown in the PAS/Discovery applications is based on information in the Link  
 15 Table and therefore a search of the PAS/Discovery database(s) is not done.  
 16  
 17 The Integration Engine pulls William R. Brown's information from the CDS  
 18 application's database and pushes it into the PAS application's database and then  
 19 launches the Discovery application to displays the newly created William R.  
 20 Brown record in the Discovery application. Ms. Baker then enters the

1 information from the Fact Finder into the Discovery application for use in the  
2 PAS application.

3  
4 When Ms. Baker is done entering the information from the Fact Finder into the  
5 Discovery application and because it is the end of the day on Friday, Ms. Baker  
6 shuts down her computer and heads home for the weekend.

7  
8  
9 Use Case 2: Pushing Person Information From One Source Application Into  
10 Another Destination Application

11  
12 On the following Monday, Ms. Baker is scheduled to meet with Mr. Brown for an  
13 implementation meeting. During this meeting she will use the ISP application.  
14 To save time and eliminate re-keying of data, client specific information from the  
15 CDS application will be pushed into the ISP application.

16  
17 In preparation for the meeting with Mr. Brown, Ms. Baker turns on her computer,  
18 which automatically launches the Dashboard. The Working Client is set to Mr.  
19 Brown and the Working/Source Application is still set to the CDS Application as  
20 evidenced by the caption "Working Client: William R. Brown (CDS:)" in the  
21 Status area of the Dashboard.

1

2 Ms. Baker then clicks on the "ISP" application button on the Dashboard to push  
3 information about Mr. Brown from the CDS application into the ISP application.  
4 Note: since Ms. Baker previously checked the "Don't ask" check box, no dialog  
5 box appears. Thereafter, the ISP application automatically launches and displays  
6 Mr. Brown's record.

7

8

### 9 Use Case 3: Pushing Client Specific Information From One Source Application 10 Into More Than One Destination Application

11

12 The next day, Ms. Baker must use both the PLAM and the EA applications  
13 because she successfully sold an insurance policy and an investment account to  
14 Mr. Brown. Rather than following an application-by-application workflow, she  
15 decides (as a sophisticated user) to populate these applications at the same time  
16 with Mr. Brown's information.

17

18 Hence, Ms. Baker turns on her computer, which automatically launches the  
19 Dashboard. Again, the Working Client is set to Mr. Brown and the  
20 Working/Source Application is set to the CDS Application as evidenced by the

1 caption "Working Client: William R. Brown (CDS)" in the Status area of the  
2 Dashboard.  
3  
4 Using the Dashboard, Ms. Baker clicks on the "Search" button, launching the  
5 Search applet. The applet forms are automatically populated with information  
6 from the Working Client. Ms. Baker selects the PLAM and EA applications and  
7 then clicks on the "Synchronize" button to push Mr. Brown's information from  
8 the CDS application to the PLAM and EA applications  
9  
10 After synchronization is complete, Ms. Baker clicks on the "EA" button, which  
11 launches the EA application and displays Mr. Brown's record created in the EA  
12 application as a result of the "Synchronize" action. After completing the EA  
13 application, Ms. Baker launches the PLAM application through the Dashboard in  
14 the same manner.  
15  
16  
17 Use Case 4: Searching For A Person  
18  
19 After taking an extended leave of absence from work, Ms. Baker cannot recall  
20 who she previously worked on and entered into the various applications.

1 Furthermore, during her leave her assistant Ms. Green worked on several cases,  
2 which Ms. Baker is unaware of.

3  
4 To get up to speed, Ms. Baker turns on her computer, which automatically  
5 launches the Dashboard. However, the Working Client is no longer set to Mr.  
6 Brown but to a different client.

7  
8 When Ms. Baker receives calls from unfamiliar people, she clicks on the "Search"  
9 button on the Dashboard and uses the name search function. She can then launch  
10 into each application from the list of people displayed in the results area of the  
11 search window by double-clicking on a person's row or by highlighting the person  
12 and clicking on the "Launch Application" button. Using this method, she can get  
13 background information on each person she has searched.

14  
15

#### 16 Use Case 5: Synchronizing Information

17

18 Later that day, Ms. Baker realizes that while she had linked Mr. William R.  
19 Brown together, his address information is not the same across all of the  
20 applications.

21

1 Thus, Ms. Baker brings up all occurrences of William R. Brown using the  
2 Dashboard "Search" button. All of the same William Brown rows are  
3 highlighted. She realizes that she missed an occurrence of William R. Brown in  
4 another application. She highlights that row as well and then clicks on the  
5 "Synchronize" button.

6  
7 Ms. Baker confirms that the freshest information is in the CDS application. She  
8 knows that the currently highlighted row in the results list will be used as the  
9 source of the freshest information. By default, the currently highlighted row is the  
10 "Working Client" row. She recognizes the currently highlighted row because it is  
11 highlighted differently from the others. The other occurrences of Mr. Brown will  
12 be updated with the information from the CDS application.

13  
14 After synchronization, the search result list is refreshed with the updated  
15 information.

16  
17 Finally, FIGS. 17-22 are representations of user interface screens depicting  
18 aspects of the present invention described hereinabove.

19  
20 CONCLUSION

21

1 Having now described a preferred embodiment of the invention, it should be  
2 apparent to those skilled in the art that the foregoing is illustrative only and not  
3 limiting, having been presented by way of example only. All the features  
4 disclosed in this specification (including any accompanying claims, abstract, and  
5 drawings) may be replaced by alternative features serving the same purpose, and  
6 equivalents or similar purpose, unless expressly stated otherwise. Therefore,  
7 numerous other embodiments of the modifications thereof are contemplated as  
8 falling within the scope of the present invention as defined by the appended  
9 claims and equivalents thereto.

10

11 Moreover, the techniques may be implemented in hardware or software, or a  
12 combination of the two. Preferably, the techniques are implemented in computer  
13 programs executing on programmable computers that each include a processor, a  
14 storage medium readable by the processor (including volatile and non-volatile  
15 memory and/or storage elements), at least one input device and one or more  
16 output devices. Program code is applied to data entered using the input device to  
17 perform the functions described and to generate output information. The output  
18 information is applied to one or more output devices.

19

20

1 Each program is preferably implemented in a high level procedural or object  
2 oriented programming language to communicate with a computer system,  
3 however, the programs can be implemented in assembly or machine language, if  
4 desired. In any case, the language may be a compiled or interpreted language.  
5  
6 Each such computer program is preferably stored on a storage medium or device  
7 (e.g., CD-ROM, hard disk or magnetic diskette) that is readable by a general or  
8 special purpose programmable computer for configuring and operating the  
9 computer when the storage medium or device is read by the computer to perform  
10 the procedures described in this document. The system may also be considered to  
11 be implemented as a computer-readable storage medium, configured with a  
12 computer program, where the storage medium so configured causes a computer to  
13 operate in a specific and predefined manner.  
14  
15